



X-Series Batteries



User Manual



- ### Features
- Quick removal for portability.
 - Built in BMS
 - Ice blue battery level indicator for easy indication during use.
 - Industrial design casing to fit with the aesthetic of the CYC mid-drive system line-up.
 - Custom made gasket.
 - Magnetic battery mount helps to prevent the frame and battery components from damage upon impact.

General Specifications

	X-36	X-52	X-52L
Battery Cells	Samsung 40T 21700 cells		
Battery Voltage	36V (2p10s)	52V (2p14s)	52V (3p14s)
Battery Capacity	8Ah (288Wh)	8Ah (416Wh)	12Ah (624Wh)
Maximum Continuous Discharge Current	60A	60A	80A
Maximum Charge Current	2A	4A	4A
Weight (with Mount & Magnets)	2.8 kg	3.7 kg	5 kg

*** Compatible X1 Pro Gen 1, X1 PRO Gen 2, X1 Stealth

Dimension

X-36

- 218mm (L) X 107mm (W) X 119mm (H)

X-52

- 274mm (L) X 107mm (W) X 119mm (H)

X-52L

- 317mm (L) X 107mm (W) X 130mm (H)

Magnetic Battery Mount

- 173mm (L) X 92mm (W) X 15mm (H)

Ø48 Magnet & Straps (2pcs)

- Ø48mm X 9.6mm (H)

*** 58V 2A XT90 Charger Provided