

B-SERIES BATTERIES



CE FC RoHS



FEATURES

- HIGH DISCHARGE BMS WITH SHORT CIRCUIT PROTECTION
- SECURE & VERSATILE DUAL-MOUNTING SOLUTION
- ORIGINAL HIGH QUALITY SAMSUNG 21700 CELLS
- STEALTHY & COMPACT BAG-LIKE DESIGN
- ICE-BLUE BATTERY LEVEL INDICATORS
- QUICK REMOVAL FOR PORTABILITY
- WEATHER & IMPACT RESISTANT
- FAST CHARGING CAPABILITIES

GENERAL SPECIFICATIONS



Product	B-36	B-52	B-52	B-52L	B-52L
Rated Voltage	36V 10s2p	52V 14s2p	52V 14s2p	52V 14s3p	52V 14s3p
Capacity	10Ah (360Wh)	10Ah (520Wh)	8Ah (416wh)	15Ah (780Wh)	12Ah (624Wh)
Cell	Samsung 50e 21700	Samsung 50e 21700	Samsung 40T 21700	Samsung 50e 21700	Samsung 40T 21700
BMS Rating	30A continuous discharge	30A continuous discharge	70A continuous discharge	45A continuous discharge	70A continuous discharge

*THIS PRODUCT COMPLIES WITH UN38.3, IEC62133, FCC, & CE STANDARDS

DIMENSION

B-36




210mm (L) x 81mm (W) x 112mm (H)

B-52



274mm (L) x 81mm (W) x 112mm (H)

B-52L



377mm (L) x 81mm (W) x 112mm (H)



SCAN HERE FOR
QR CODE